

**DFM 4 and DFM 8 Media**

Fiber Bond's diffusion media consists of a blend of synthetic fiber sizes, bonding agents and a unique adhesive that coats every fiber. The result is uniform, high-quality filtration.

**Rolls • Blankets • Pads • Panels**

**DFM 4 Media****Media Specifications**

**Nominal Thickness**  
1 Inch (25 mm)

**Weight**  
16.2 opsy  
(549 grams M<sup>2</sup>)

**Master Roll**  
80" x 66'  
(2M x 20M)

**DFM 4  
1" Media**

When used as a ceiling filter in downdraft booths, DFM 4 diffuses the air creating an even laminar flow throughout the booth.

**DFM 8  
1/2" Media**


DFM 8 is typically used in crossdraft spray booths. Its unique design assures directional stability of the air flow.

**DFM 8 Media****Media Specifications**


**Nominal Thickness**  
0.50 Inch (13 mm)

**Weight**  
11.6 opsy  
(393 grams M<sup>2</sup>)

**Master Roll**  
80" x 135'  
(2M x 41.1M)

**DFM Internal & External Support Panel Filters****DFM Panels  
Ideal For Installations  
With Limited Access**

Internal support offers a 9-gauge grid sealed between the media. External support has an "X" grid on the air exiting side of the panel.



**Downdraft Paint Booth**

DFM 4 media utilized as a ceiling filter in a downdraft paint booth.

**DFM 4  
Specifications****Nominal Thickness**  
1 Inch (25 mm)**Weight**  
16.2 opsy  
(549 grams M<sup>2</sup>)**Master Roll**  
80" x 66"  
(2M x 20M)**DFM 8  
Specifications****Nominal Thickness**  
0.50 Inch (13 mm)**Weight**  
11.6 opsy  
(393 grams M<sup>2</sup>)**Master Roll**  
80" x 135"  
(2M x 41.1M)**DFM 4 Media****DFM 8 Media****DFM Panel Filters****Diffusion media test report is available by  
contacting Fiber Bond at (219) 879-4541.**